

4T MOTORCYCLE OIL ADDITIVE PACKAGE T3069

● Introduction

The four stroke motorcycle oil package T3069 is composed of various high quality components. It has good high temperature detergency, low temperature dispersity, anti-oxidation, anti-wear and other property. It can be used to lubricate three parts of engine, clutch and transmission at the same time. With different treat rate in the appropriate base oil, it can blend oil with performance levels of 10w/30, 10w/40 & 15w/40, it can meet API SL, SJ and other performance requirements.

● Recommended Treat Rate (wt%)

Performance Level	Treat Rate (wt%)
SL	6.0
SJ	5.5
SG	5.0
SF	4.5

● Specifications

Item	Typical Value	Test Method
Appearance	Brown Viscous Liquid	Visual
Density (20°C), kg/m ³	Report	GB/T 13377
Kinematic Viscosity (100°C), mm ² /s	Report	GB/T 265
Flash Point (COC), °C	≥180	GB/T 3536
Total Base Number, mgKOH/g	100	SH/T 0251
Nitrogen, wt%	0.8	SH/T 0224
Zinc, wt%	2.1	ASTM D5185
Calcium, wt%	3.1	ASTM D5185
Phosphorus, wt%	1.8	ASTM D5185

● Package, Handle & Storage

1. Packed in 200L metal drum, IBC-Tank or made to order.
2. Long term storage temperature should not exceed 45°C.
3. Handle & blending temperature should not exceed 65°C.
4. Not dangerous chemical, store in dry & clean warehouse.